

INFRARED PYROCERAM COOKING RANGE 4 AREAS

Electric range with pyroceram surface with AISI 304 stainless steel structure, 12/10 mm thickness top. Cooking surface in pyroceram, flush with worktop and sealed. Heating by infrared electric elements. 4 cooking independent areas controlled by energy regulator.



<i>Hob composition</i>	2 areas Ø cm 17.5 (1,7 kw) + 1 areas Ø cm 23 (2,5 kw)	<i>Power supply</i>	Electricity
------------------------	---	---------------------	-------------

<i>Product fitting up</i>	Counter Top
---------------------------	-------------

Functional features

- 4 independent cooking areas, power rated at 2 x 2.5 kW and 2 x 1.7 kW.
- Power regulator, 10 levels.
- Incandescent electric elements, 2 area Ø 175 mm and 2 area with double circuit external Ø 230 mm and internal Ø 155 mm.
- Double functionality: it is possible to use different types of pot on the same plate.
- Easy to clean thanks to a smooth, hermetic glass ceramic surface.
- Installations through suitable accessories: on under compartment, bridge solution.

Constructional features

- Work top made in AISI 304 stainless steel, 12/10 thickness, with Scotch Brite finish.
- Structure and control console made in AISI 304 stainless steel with Scotch-Brite finish.
- Side-by-side top juxtaposition very rigid and accurate guaranteeing max quality and hygiene.
- Cooking surface in pyroceram, thickness 6 mm, flush with worktop and sealed, max load weight: 0.2 kg/cm².
- Hob dimensions: 65 x 55 cm.
- Heat-resistant knobs with screen printed markings and reference index printed on control console.
- Rear slot with perimeter edge for liquids collection with enamelled guard.
- Access to all components through front compartment and control console.

Safety equipment and approvals

- Thermal protection for over temperature intergated on the plate.
- Residual heat indicator light under glass.
- CE approvals in respect of all directives and regulations.
- Approval to European Standard EN 1672-2 Hygienic Design.
- IPX5 protection rating.

Technical Data

<i>Working voltage</i>	400V 3N~ / 230V 3~ / 50÷60 Hz	<i>Net Weight</i>	32 kg
<i>Gross Weight</i>	46 kg	<i>Electric Power</i>	8,4 kW
<i>Dimensions</i>	70x70x24 cm	<i>Packing</i>	82x76x68 cm