

0G0BME

ELECTRIC WET WELL BAIN-MARIE, COUNTER TOP VERSION



RANGE FEATURES

- Top: 18-10 stainless steel (12/10 mm gauge)
Free-standing structure with top, front panels, sides and control consoles in 18-10 stainless steel; back panels in stainless steel.
Top, sides, back, front panels and control consoles with satin scotchbrite finish.
Side-by-side top configurations with secure fixing between units.
IPX5 protection rating on all units.
CE approval of all gas products.



FUNCTIONAL FEATURES

- Well sealed into the top with condensation collection recess. Pressed well with rounded corners and sloping base for front drainage.
- Well internal dimensions: 305x510x160h mm, suitable for 1X1/1 GN h=150 mm container.
- Thermostatic temperature control from 30° to 90°C.
- Thermal safety cutoff to prevent boiling dry.
- Front-mounted drain cock with safety control to prevent accidental opening.
- The bain-marie can be equipped with: stainless steel containers with different dimensions, stainless steel cross-bars.
- Heat-resistant knobs with screen printed markings and reference index printed on control console.
- Predisposed for connection to other Gamma series elements.



TECHNICAL FEATURES

- Well in AISI 304 18-10 stainless steel, thickness 10/10.
- Water capacity indicated by operating level 6 litres. Specific heating output 241 W/litre.
- Maximum temperature safety thermostat at minimum allowed water level (stamped on well) to avoid boiling dry.

| | | | | |
|-------------------|-----------|-----------|----------------------------|----------------------------------|
| Width | Cm | 35 | | |
| Depth | Cm | 70 | Electric Power | kW 1,6 |
| Height | Cm | 24 | | |
| Net weight | Kg | 50 | Standard connection | V-Hz 230V 1N~ / 50 ÷ 60Hz |