Vizion





VZN T5 Series

VIZION offers systems that assure the highest quality ingredient water at the lowest cost of ownership for premium water filtration. The VZN series couples that assurance with a lower total cost of ownership and smaller footprint.

The VZN systems use self-cleaning ultra filtration ahead of a low-cost carbon cartridge to separate mechanical filtration from taste and odor reduction. This self-cleaning and separation assures the full stated life expectancy of the carbon cartridge and provides it with mechanically pure water, which eliminates premature clogging. These technologies are then followed by template-assisted crystallization to protect your equipment against lime scale buildup.


The VZN systems provide a lower total cost of ownership, ensuring you have an immediate measurable return on your investment compared with your existing system.

FEATURES AND BENEFITS:

- Separation of mechanical filtration from taste and odor reduction assures long time between cartridge changes.
- Assures only one low-cost carbon cartridge change per year.
- Self-cleaning particle reduction assures low maintenance costs.
- .015 micron ultra filter removes particles
 33 times finer than the next best system,
 assuring consistent high quality water.
- TAC cartridge reduces lime scale by 96–98% without using chemicals or wasting water.
- Maintains good water minerals that provide benefits to customers' health while also creating high-quality drinks.
- Small footprint ideal for foodservice market.
- Several configurations available.


Vizion

VZN T5 Series



Model &	Height	Width	Depth	Operating
Mfg. No.	(A)	(B)	(C)	Weight
VZN-421H-T5	39"	31 <i>"</i>	9"	82 lbs.
9700730	(99 cm)	(79 cm)	(23 cm)	(37 kg)
VZN-441H-T5	39"	50"	9"	98 lbs.
9700750	(99 cm)	(127 cm)	(23 cm)	(44 kg)

Plumbing	Connections
Fiullibilig	Connections



Electrical Ratin	gs and Plug	Configurati	ons	
Model & Mfg. No.	Volts	Watts	Amps	Hertz
VZN-421H-T5 9700730	100–240	10	.08	50/60
VZN-441H-T5 9700750	100–240	10	.08	50/60

NOTE: Includes plug adaptors for US, Europe, Australia, and UK.

Capacities					
Model & Mfg. No.	Capacity Per Minute	Carbon Lifespan	UF Length	No. of Carbon Elements	No. of TAC Cartridges
VZN-421H-T5 9700730	6.6 gal. (25 liters)	1 year	20" (51 cm)	1	1
VZN-441H-T5 9700750	13 gal. (49 liters)	1 year	40" (102 cm)	1	1

Specifications (Ultra Filter)				
Maximum Operating Pressure	100 psig (690 kPa)			
Maximum Operating Temperature	104°F (40°C)			
Nominal Pore Size	.015 microns			
pH Range	3-10			
MWCO	100–150 kD			



A.J. Antunes & Co.
Headquarters/Manufacturing
180 Kehoe Boulevard
Carol Stream, Illinois 60188 USA
Phone (630) 784-1000
Toll Free (800) 253-2991
Fax: (630) 784-1650

Antunes Equipment Manufacturing (Suzhou) Ltd., 9 Hou Ju Road, Building #24, S&T Park, SND Suzhou, Jiangsu, China 215011 Phone: 86-512-6841-3637 Fax: 86-512-6841-3907

www.ajantunes.com